

Focus Internal PIR C/W Wall/Ceiling Bracket

Features: Dual Element Pyro Sensor, S.M.D Technology, 12 Meter, 110° Convex Honey Comb, Hemispherical, Fresnel Lens, Thermal Optic Protection Cavity, Excellent False Alarm Suppression, Walk Test LED High RFI & EMI Immunity, Pulse Count 1, 2 & 4 Jumper selectable, Universal Wall, Ceiling Mounting Bracket Grade I.



Product Specification

General Specifications

Type	Dual element pyro sensor
Digital pulse count	1, 2 & 4 jumper selectable
Mounting	Wall/ceiling bracket

Operation Specifications

Alarm period	Greater than 2 seconds
Mounting Height	2m
Detection Speed	0.3—3ms
Range	12m 110° volumetric

European Standards:

Electro-magnetic Compatibility (EMC) 89/336/EEC (Amended by 92/31/EEC and 93/68EEC) RoHS

Order Code

LY15-016-33

Electrical Specifications

Operating voltage	9-16Vdc
Operating current	8mA
Alarm contacts	Normally closed dry contacts (0.5A/24V)
Tamper contacts	Normally closed dry contacts (0.5A/24V) with 15Ω resistor in series
Storage temperature	-10 to + 50°C

Technical Specification

Plastic housing material	ABS
Dimensions	100mm X 65mm X 45mm
Weight	100g